

Product Category		Bus: A with Ford Transit	
Category Description	Base Spec and Description	Option	
Chassis Options			
AIR CLEANER (ENGINE)	Manufacturer standard		
ALTERNATOR	Manufacturer standard		
AXLE, FRONT: MINIMUM LOAD	By capacity. Minimum 4,130 lbs.		
AXLE, REAR: MINIMUM LOAD	By capacity. GVWR Total 9,000lbs for 138" and 9,500 for single rear wheel and 10,360 for dual rear wheel 156".		
AXLE, REAR GEAR DIFFERENTIAL	Manufacturer Standard		
BATTERIES	Shall comply with National Standard. Gasoline Transit comes standard with dual 610 CCA batteries. Diesel Transit comes standard with dual 760 CCA batteries.		
BRAKES, ABS, HYDRAULIC DISC FRONT AND REAR	Must meet Section 257.1813 of Section 13 of PA187 of 1990. ABS to meet FMVSS #121. Hydraulic Disc ABS front and rear.		
BRAKES, PARKING	Shall comply with State and National Standards.		
BUMPER, FRONT	Shall comply with National Standards. Must be painted black.		
	Add 6 in. yellow numbers on bumper (state qty)		C1590
CHASSIS	Ford Transit		
CIRCUIT BREAKERS	Shall comply with National Standards and State Specifications		
COOLANT RECOVERY (ENGINE)	Must include some means for visual or electronic checking of coolant level without removing tank cap or releasing pressure from cooling system. All hoses shall be heavy duty rubber material.		
CRUISE CONTROL	None		
	Add cruise control		C1630
CLIPBOARD HOLDER	None		
	Add clipboard holder in drivers area		C1650
DRIVESHAFT GUARDS & SHIELDS	Shall comply with National Standards.		
ENGINE	Gasoline, minimum 3.7 L; provide power curve to include horsepower, RPMs, torque, and fuel economy. Complete engine specifications and warranty information required.		
	Ford 3.2 L Diesel		C1655
ENGINE SOUND DEADENING PACKAGE	Required in engine compartment, hood and firewall. Interior sound level shall comply with National Standards		
EXHAUST SYSTEM	Must exit at rear bumper.		
FIRE SUPPRESSION SYSTEM	None - Engine Compartment		
	DRY CHEMICAL SYSTEM - to be located in the engine compartment and be automatically activated when the fire detector has sensed a fire in the engine compartment. The system must also include a mechanism for activation by the driver. Include a lamp or buzzer to alert the driver when the system has been activated.		C2360

Product Category		Bus: A with Ford Transit
	WATER/FOAM SYSTEM - to be located in the engine compartment and be automatically activated when the fire detector has sensed a fire in the engine compartment. The system must also include a mechanism for activation by the driver. Include a lamp or buzzer to alert the driver when the system has been activated.	C2365
FRAME SIDE MEMBERS	Must comply with National Standards	
FUEL TANK	Manufacturer Standard- 25 gallon minimum. Must comply with National Standards.	
FULL INSTRUMENTATION PACKAGE (ENGINE)	Shall comply with National Standards, and all gauges shall be in English-no Metric.	
FOG LIGHTS	None	
	Add fog lights	C2440
HEADLIGHTS	Shall comply with National Standards. Daytime running lamps (DRL) shall be provided.	
HEATER BLOCK, INTERNAL (ENGINE)	None	
	Add block heater	C2470
HORNS	Shall comply with National Standards.	
HOSES (ENGINE)	Shall comply with National Standards.	
IGNITION SWITCH (ENGINE)	Controlled running and shutdown shall require electrical current provided by the ignition switch in ON, RUN and ACCESSORY positions	
LINE-SET TICKET	Manufacturer shall include with delivery of vehicle a line-set ticket that will reflect all chassis components, GAWR for both front and rear axles and GVWR. Web based is acceptable	
PAINT & FINISH, EXTERIOR	Must be Polyurethane or equal and a 5-year warranty and must meet State and Federal Standards.	
	Additional after factory undercoating	C2610
PAINT, WHEELS	All wheels shall be painted per National Standards	
	Paint wheel black	C2620
	Paint wheels white	C2640
	Paint wheel gray	C2650
RIMS	Shall comply with National Standards.	
RUST PROOFING	Underbody and firewall to be fully insulated and undercoated with rust proofing compound.	
SHOCK ABSORBERS	Front and rear, heavy-duty double-acting, piston type that are adequate size and axle load for the axle capacity.	
STEERING	Factory installed heavy-duty power steering with tilt.	
SUSPENSION, AXLE FRONT	Manufacturer Standard	

Product Category		Bus: A with Ford Transit	
SUSPENSION, AXLE REAR		Manufacturer Standard	
SWITCHES, IGNITION		Shall comply with National Standards.	
TIRE & RIM, SPARE		None. Must be dealer negotiated.	
TIRES, TUBELESS RADIAL		235/65R16 (SRW) / 195/75R16 (DRW)	
TOW HOOKS		2 mounted to rear of frame	
TOW BAR		None	
TRANSMISSION, AUTOMATIC		6-speed, heavy duty cooling	
TRANSMISSION, OIL		Shall comply with National Standards	
TRANSMISSION, WARRANTY		Shall comply with National Standards	
TURN SIGNALS		Shall comply with National Standards	
WARRANTY		Provide Manufacturer Standard	
WHEELBASE, GVWR		To be compatible with size of bus	
WIRING		Shall comply with National Standards. The wiring shall be arranged in circuits, as required, with each circuit protected by a fuse breaker or electronic protection device. See also Electrical Wiring	
OPTIONAL OR EXTENDED WARRANTY		Dealer Negotiated	
Body Options			
ACCESS/FRONT BULKHEAD COMPARTMENT		None	
AIR CONDITIONING, IN DASH		OEM standard	
AIR CONDITIONING		None; When choosing air conditioning it may not be compatible with other options and it must be verified with vendor.	
		Minimum 45,000 BTU	B1030
		Minimum 55,000 BTU	B1040
		60,000 plus BTU - Dual Compressor tied with skirt mounted compressor	B1050
AIR CONDITIONING. IN WALL SYSTEM		None	
		Add in wall recessed system	B1350
AIR CONDITIONING. ROOF TOP CONDENSER		None	
		Add roof top condenser for air conditioning	B1360
AISLE STRIPS		Shall comply with National Standards.	
		Stainless steel	B1410
		Vinyl	B1430
		Aluminum	B1450
BACK UP ALARM AND STICKER		Shall comply with National Standards.	
BATTERY SLIDE OUT TRAY		None	
		Add battery box	B1520
BODY DATA PLATE		Will be mounted in a clearly visible location inside body stating seating capacity, year manufactured, etc.	
BODY MOUNTING		Per manufacturers standards and must meet State and Federal Standards.	
BUMPER, REAR		Shall comply with National Standards and shall be painted glossy black matching National Standard #595A - Color 17038.	

Product Category		Bus: A with Ford Transit	
BUS LOCK UP SYSTEM	None		
	Back only		B1550
BODY LOCKS KEYED ALIKE	Shall comply with National Standards.		
BUZZERS/AUDIBLE SIGNAL/ALARMS	Shall comply with National Standards. See Doors and Windows sections for additional information.		
CROSSING GATE ARM	None		
	electric crossing gate arm		B1810
CROSSING GATE ARM INTERRUPT SWITCH	None		
	Add crossing gate arm interrupt switch		B1840
DEFOGGER FANS	None		
	Add 1 6 in. 2 speed defogger fan		B1920
DELIVERY, EXTENDED	Normal delivery upon manufacturers receipt of purchase order. For other delivery options contact dealer		
DOOR, ENTRANCE	Entrance Door, passenger. Base Spec: Shall be manual, double-out split-type located at right front of bus with padded header over entrance door. Double bearing chromium plated mechanical control shall be mounted within comfortable reach of the driver and meet National Standards.		
	Electric, double out, split type		B1980
DOOR ENTRANCE SWITCH	OEM standard-electric operated door		
ELECTRICAL EQUIPMENT & WIRING	Must meet SAE and National Standards. Shall be inside body channel readily accessible through removeable panels. All harnesses and wiring shall be protected from wall metal structure. All bodies shall be equipped with an electrical curcuit master switch and will cut body circuits "ON" and "OFF" by means of a master switch solenoid controlled by the ingnition switch (mounted in electrical compartment for aftermarket components only), controlled by ignition switch. See Wiring for additional information		
EXIT, EMERGENCY DOOR	All emergency exits shall conform to FMVSS #217 and all applicable State and Federal laws.		
EXIT, EMERGENCY DOOR, GLASS GUARD			
	Add glass guard on lower section of rear emergency door		B2155
EXIT, EMERGENCY WINDOW	All emergency exits shall conform to FMVSS #217 and all applicable State and Federal Laws.		
EXIT, ROOF HATCH	All emergency exits shall conform to FMVSS #217 and all applicable State and Federal Laws.		
	Deduct roof hatch		B2190
	Transpec (state qty)		B2250

Product Category		Bus: A with Ford Transit	
EXIT, ROOF HATCH, POWER VENT	None	Power vent for front or rear (state quantity)	B2310
ROOF VENT, STATIC FENDERETTES	Shall comply with National Standards		
	None	Rubber fenderettes	B2350
FLOOR COVERING	Shall comply with National Standards		
		Colored floor and step treads. Please notify and verify availability of color of choice.	B2510
FLOOR: SUBFLOOR PLYWOOD	Floor shall be 1/2" exterior grade treated plywood		
		1/2" marine grade plywood	B2540
		5/8" marine grade plywood	B2541
FLOOR: SUBFLOOR JOINTS SEALED	Base Spec: None		
		All subfloor joints water proof sealed	B2550
FLOOR COVERING ONE PIECE	See floor covering spec		
FUEL FILLER DOOR	Part of door frame. Open the driver door and this exposes the fuel fill in the frame of the door. Lock on door locks access to the fuel fill		
GLASS ENTRANCE DOOR	Safety glass upper and lower; shall comply with National Standards and FMVSS		
GRAB RAIL AT ENTRANCE	Stainless steel grab rail shall be provided at front entrance on left side securely mounted inside body close to bottom step for small children to reach and shall be designed to eliminate possibility of students clothing or personal items to become lodged or stuck upon exiting the bus		
		Add right side grab rail.	B2750
HEADROOM	Shall comply with National Standards. Minimum 73" headroom; Minimum 69" on single rear wheel		
		73 inch headroom for single rear wheel	B2800
HEATER/DEFROSTERS	Suspended for full heating action, minimum output 40,000 BTU single fan output located to rear of wheel house, heater pipe to be covered. driver heater is OEM supplied. No silicone hosing		
HEATER, HOSES	Heater hoses shall be heavy duty and comply with National Standards. Contact dealer for other options, pricing, and availability.		
HEATER HOSE CLAMPS	Shall comply with National Standards.		
		Change to constant torque clamps	B3060

Product Category		Bus: A with Ford Transit	
INSULATION		Shall comply with National Standards. Roof and side walls shall be fully insulated including body bow cavities. Each bidder shall supply complete information on insulation. Premium type of insulation with the body will be considered standard. Noise package should be a separate line item.	
LETTERING, IDENTIFICATION, & TRIM		Must meet State and National Standards. Lettering specifics provided by each school district. Reflective markings: must be reflective tape as follows: 1" tape outlining all exits. Each bus shall be numbered with numbers assigned by the school district and made of vinyl type. Numbers will be four locations where numbers will be placed (front, sides and rear) All lettering shall be 6". Reflective package: 2" tape below beltline on both sides, 1" tape completely outlining rear of bus from below cap to rear bumper, School Bus lettering front and rear.	
		3M brand tape	B3100
LETTERING; INTERIOR SEAT #'S		None	
		Add numbers for interior seats; 2" decal (state quantity)	B3120
LETTERING; ROOF TOP NUMBERS		None	
		Add 24 inch numbers (state qty of digits). Price is per digit	B3130
LICENSE PLATE HOLDER		Shall be on left rear outside of body with suitable method for mounting license plate	
LIGHT MONITOR, EXTERIOR LIGHTS		None	
		Light monitor system LED	B3290
		Light monitor system not LED	B3300
LIGHT, LANDING		Next to entrance door, outside skirt mounted	
		Delete landing light	B3310
		Change to LED type light	B3320
LIGHT, LED STEPWELL LAMP		None	
		Add LED stepwell lamp	B3360
LIGHT, STROBE		Strobe light is required. Shall comply with State and National Standards.	
		Add Brush guard	B3430

Product Category		Bus: A with Ford Transit	
LIGHTS		Lighting system shall be Weldon 7000 transistorized flasher OR EQUAL OR MULTIPLEX control units and shall include turn signals, stop lights, marker lights, stepwell lights, parking lights, landing light, interior lights, and eight (8) light warning system. Rear directional signal, side directionals, stop lights, and back-up lights in addition to the regular stop lamps. All exterior lights shall be bulb and conform to National Standards. (8 way lights include 3" black band around)	
		Change 8 way only to strobing LED	B3460
		Change only the tail, brake, turn and backups to LED style lamps	B3470
		Change 8 way, tail, brake, back up and turn to LED style lamps	B3480
LIGHTS, CLEARANCE		Manufacturers standard clearance lights and must meet State and Federal Standards.	
		Add armored marker	B3490
		Change to LED style	B3500
		Add armored marker and add LED style	B3510
LIGHT, EMERGENCY DOOR		None	
		Add Red ICC light over emergency door (State quantity)	B347
LIGHTS, INTERIOR		There shall be 4 dome lights installed to include 1 in drivers compartment and 3 in passenger compartment. The landing light shall be activated when the door opening mechanism is initiated.	
		LED Dome lights	B3530
		Add maximum dome lights	B3560
		Add maximum led dome lights	B3570
LIGHTS; INTERIOR DRIVER DOME		Included	
		Delete drivers dome	B3580
LIGHTS TAIL TURN FLUSH MOUNT			
		Stop tail 4" flush mount LED	B3600
LIGHT VISORS		None	
		Individual visors for warning lights in lieu of visors that cover amber and red lights.	B3620
LOCKS, DOOR		Standard	
		Delete	B3635
MIRRORS, CROSSOVER		Shall come equipped with two convex elliptical cross-view mirrors mounted on front of vehicle. Shall be heated. Contact dealer for options and pricing	
MIRRORS, SIDE		Body shall be equipped with two split - style-type side-view mirrors supported from top or bottom. Shall be heated. Contact dealer for options and pricing.	
		remote, heated	B3940
MIRRORS BRACKETS		Shall comply with National Standards.	
MIRROR, TIMER		None	
		Timer for heated mirror	B3990

Product Category		Bus: A with Ford Transit	
MIRROR, INSIDE REAR-VIEW		An overhead mirror mounted above driver and a glass mounted chassis oem shall be included	
MUD FLAPS		2 rear attached appropriately and made of rubber material.	
NOISE REDUCTION SYSTEM		Shall comply with National Standards.	
		Acoustical headliner full length of bus	B4070
NOISE REDUCTION FIREWALL		Included	
PAINT & FINISH		Body shall be painted with polyurethane and according to specifications as set forth by the National Standards, which shall include all words, letters and numbers to meet those specifications.	
PAINT, ROOF		Roof shall be white.	
PANELING, EXTERIOR		Side skirts between the front and rear axles shall extend down to within two inches plus or minus of the horizontal line from the center of the front spindle to the center of the rear axle on new unloaded bus on flat, level surface. Side skirt length may extend lower than this requirement. Exterior paneling includes sheet metal skin forming exterior surface of body and shall be 20-gauge steel minimum thickness and be attached to bow frames and strainers to act as an integral part of structural frame.	
		Aluminum panels	B4260
PANELING, INTERIOR		Interior body shall be lined with panels securely fastened to adjoining parts. All joints are to be covered. No sharp edges will be left; molding shall be securely fastened so dirt will not readily work under it. Interior paneled areas immediately below window line shall be galvanized embossed steel, aluminum in color. Exposed edges shall be beaded, hemmed, flanged, or treated to eliminate sharp edges.	
PANEL, SHOULDER PAD		None	
		Full bus length	B4310
POWER SOURCE		Per OEM	
RADIO SYSTEM		AM/FM/CD	
		Downgrade to PA only	B4520
		Add PA to radio	B4550
RADIO SYS. WITH EXT. PA & SPEAKER		None	
		Add exterior speaker	B4560
REFLECTORS		2 amber reflectors on each side of bus near the front and 2 red on rear side panels, 2 red on rear panels, and 2 amber intermediate on sides-Shall comply with FMVSS	
RUB RAILS		3 applied rub rails	

Product Category		Bus: A with Ford Transit
	Add fourth rub rail	B4610
RUST PROOFING	Must be fully rust proofed including battery compartment, State Manufacturer Standard	
SAFETY EQUIPMENT	Per KAR (Kansas Administrative Regulation) 91-38-2. (1) Each school bus shall contain the following emergency supplies: (A) At least one 2A-10BC fire extinguisher; (B) at least one readily identifiable first aid kit in a removable, waterproof, and dustproof container; (C) at least one readily identifiable body fluid clean-up kit, in a removable, water proof, and dustproof container; (D) a minimum of three reflectorized triangle warning devices, securely stored but in an accessible location. (E) a minimum of one emergency seat belt cutter./ durable webbing cutter having a full widthhandgrip and a protected, replaceable or non-corrodible blade. The required webbing cutter shall be mounted in a location accessible to the seated driver in an easily detachable manner(2) The first aid kit, body fluid clean-up kit, and fire extinguisher shall be mounted in full view of, and readily accessible to, the driver.	
SEAT, DRIVER	Base Spec: shall be manufacturer standard with adjustable positiona and three point lab/shoulder seat belt.	
SEAT, DRIVER; SEAT BELT	Seat belts for drivers with adjustable type shoulder harness are required.	
SEAT BARRIERS	Shall be equipped with the appropriate seat barriers to comply with the National Standards and FMVSS 222.	
SEATS, PASSENGER. NOTE: The school bus will be equipped with seats. The following are options.	Seats shall be supported with two-legged seat rail mounted inside the body. Padding for seats shall be as specified in National Standards Seats must meet National Standards. Minimum knee room spacing between the seats shall be 24". Fire block 42 oz. upholstery. DOT 45" high back seat.	
SEATS, FIRE BLOCK	Required	
	Upgrade to Kevlar fire block	B5070
SEATS, PASSENGER: COLOR	Shall comply with National Standards.	
	Color other than manufacturer standard. Please notify and verify availability of color of choice.	B5090
SEATS, DEDUCT FOR SEATS REMOVED	None	
	Deduct for base bid bench seats. Check with dealer for exact quantity.	B5100
SEATS 30 INCH BENCH SEAT; FLOOR MOUNT		
	30 inch floor mounted seat (state quantity)	B5110

Product Category		Bus: A with Ford Transit	
SEATS 30 INCH BENCH SEAT; TRACK MOUNT		30 inch track mounted seat (state quantity)	B5120
SEATS 36 INCH BENCH SEAT; FLOOR MOUNT		36 inch floor mounted seat (state quantity)	B5130
SEATS 36 INCH BENCH SEAT; TRACK MOUNT		36 inch track mounted seat (state quantity)	B5140
SEATS 39 INCH BENCH SEAT; FLOOR MOUNT		39 inch floor mounted seat (state quantity)	B5150
SEATS 39 INCH BENCH SEAT; TRACK MOUNT		39 inch track mounted seat (state quantity)	B5160
SEAT BELT - Lap belts shall not be installed on passenger seats in large school buses (over 10,000 pounds GVWR) except in conjunction with child safety restraint systems that comply with the requirements of FMVSS No. 213, Child Restraint Systems.		None	
SEATS 30" BENCH; FL MOUNT; INTERCHANGABLE BACK			
		30" floor mounted seat w/interchangable back (state quantity)	B5180
SEATS 36" BENCH; FL MOUNT; INTERCHANGABLE BACK			
		36" floor mounted seat w/interchangable back (state quantity)	B5200
SEATS 39" BENCH; FL MOUNT; INTERCHANGABLE BACK			
		39" floor mounted seat w/interchangable back (state quantity)	B5220
SEATS, CHILD INT. 30 " FLOOR MOUNT - comes with 2 integrated child seats.			
		30 inch seat (state quantity)	B5240
SEATS, CHILD INT. 39 " FLOOR MOUNT - comes with 2 integrated child seats.			
		39 inch seat (state quantity)	B5250
SEATS, CHILD INT. 30" TRACK MOUNT - comes with 2 integrated child seats.			
		30 inch seat (state quantity)	B5270
SEATS, CHILD INT. 39" TRACK MOUNT - comes with 2 integrated child seats.			
		39 inch seat (state quantity)	B5290
SEATS, 3 POINT, 30" FLOOR MOUNT - includes 2 point lap/shoulder belt			
		30 inch seat (state quantity)	B5430
SEATS, 3 POINT, 36" FLOOR MOUNT - includes 2 point lap/shoulder belt			
		36 inch seat (state quantity)	B5440
SEATS, 3 POINT, 39" FLOOR MOUNT - includes 3 point lap/shoulder belt.			
		39 inch seat (state quantity)	B5450
SEATS, 3 POINT, 30" TRACK MOUNT - includes 2 point lap/shoulder belt.			
		30 inch seat (state quantity)	B5460
SEATS, 3 POINT, 36" TRACK MOUNT - includes 2 point lap/shoulder belt X			

Product Category		Bus: A with Ford Transit	
		36 inch seat (state quantity)	B5470
SEATS, 3 POINT, 39" TRACK MOUNT - includes 3 point lap/shoulder belt			
		39 inch seat (state quantity)	B5480
SEATS, CHILD INT. 3 POINT, 30" FLOOR MOUNT			
		30 inch seat (state quantity)	B5610
SEATS, CHILD INT. 3 POINT, 30" TRACK MOUNT			
		30 inch seat (state quantity)	B5620
SEATS, CHILD INT. 3 POINT, 36" FLOOR MOUNT			
		36 inch seat (state quantity)	B5630
SEATS, CHILD INT. 3 POINT, 36" TRACK MOUNT			
		36 inch seat (state quantity)	B5640
SEATS, CHILD INT. 3 POINT, 39" FLOOR MOUNT			
		39 inch seat (state quantity)	B5650
SEATS, CHILD INT. 3 POINT, 39" TRACK MOUNT			
		39 inch seat (state quantity)	B5660
STORAGE POUCH KICK PANEL BARRIER		None (located behind driver on barrier)	
		Single pouch barrier	B5750
KICK PANEL		One on right side	
		Add additional left side front	B5780
STEP; DRIVER		None	
		Add Running board type step full width	B5790
STEPWELL		Stepwell shall be of non - corrosive steel, all screws and bolts shall be non corrosive steel, and shall meet National Standards. It shall contain at least one light. Step shall be covered with rubberized flooring step tread.	
STOP ARM SIGNAL		Single electric incandescent arm shall be considered standard equipment. Stop arm shall be constructed of metal ribbed or reinforced panel; such stop arm shall include wind guard and be equipped with two alternating red flashing lights. Stop arm shall meet National Standards and FMVSS #131.	
		Electric LED cluster	B5910
		Electric LED strobing	B5920
		Electric LED on STOP	B5930
STORAGE COMPARTMENT DRIVER ABOVE DRIVER		None	
		Add storage compartment above driver window	B6030
STUDENT REMINDER SYSTEM		Included. Manufacturer Standard to be triggered by warning lights	
		Delete Student Reminder System	B6080
STUDENT REMINDER ACTIVATION			
		To be armed by ignition.	B6110
		To be armed by other methods	B6120
SUNSHADE/SUNSHIELD		Shall comply with National Standards	
VENTILATION		Shall comply with National Standards	

Product Category		Bus: A with Ford Transit
WHEEL HOUSING		Shall be constructed of 18 gauge or heavier steel and be rigidly reinforced and be attached to the floor and side panels in such a manner as to prevent water or dust from entering the bus interior and shall be designed for easy removal of tires
WINDOW, REAR		Manufacturer Standard
		Tempered, Clear B6260
		Laminated, tinted B6270
WINDOWS		Windows shall be single pane split type construction safety glass to set in aluminum or steel frame. Emergency windows shall meet state specifications and National Rule 217. Windshield, service and emerg doors, side and rear windows may be equipped with max integral tinting allowed by fed, state, or ANSI standards for respective locations, except that windows rear of drivers compartment, if tinted, shall have approx 28% light transmission. Inside windows shall have marks indicating the half way point.
		Remove tint B6310
		Laminated, tinted B6320
		Laminated, clear B6330
WINDOW LINES		
		Remove window lines B6340
WINDOW, SIDE SASHES		Shall comply with National Standards.
		Painted window side sashes black B6380
WINDOW; PILASTERS		
		Paint pilasters black B6390
WINDSHIELD		Windshield to be OEM standard.
WINDSHIELD WASHER		Windshield washer fluid container is to be OEM Standard and must meet State and National Standards. Reservoir shall be full upon delivery to owner and protected to 20°F below zero
WIPER BLADES		Wipers are to be electrical, intermittent, wet arm and 2-speed. Wipers shall comply with FMVSS #104
WHEELCHAIR ENTRY		None; If selected option the lift shall be a Braun and include a lift door, lift required lights and brake/lift interlocks to meet National Standards. Includes the deduct for the 2 seats in the lift area.
		Rear lift door w/Braun. If selected option shall include a lift door, lift required lights and brake/lift interlocks to meet National Standards. Should also include the deduct for the 2 seats in the lift area. B6590

Product Category		Bus: A with Ford Transit	
WHEELCHAIR ENTRY ALT. BRANDS		None; If selected option the lift shall include a lift door, lift required lights and brake/lift interlocks to meet National Standards. Includes the deduct for the 2 seats in the lift area.	
		Change to Ricon brand lift	B6640
LIFT DOOR		Shall comply with National Standards.	
		Lock on lift door	B6650
EXTERIOR LIFT LIGHTS		Shall comply with National Standards	
		Additional Exterior lift lights	B6660
INTERIOR LIFT LIGHTS		Shall comply with National Standards	
		Additional interior lift lights	B6670
FLAT FLOOR PACKAGE (NO SECUREMENTS)		None; If selected to include all body and chassis equipment needed for flat floor. Contact Dealer before selecting this option.	
		Add flat floor package. If selected to include all body and chassis equipment needed for flat floor.	B6690
FLOOR TRACKING SYSTEM (NO SECUREMENTS)		None	
		4 floor rows/1 row over window/L-track. Includes 4 floor rows, 1 row over windows, L-track. State quantity of wheelchair placements. SecUREMENTS or seats not included. When choosing floor tracking systems, you will need to deduct seats. Deduct approximately 2 seats per wheelchair station. Check with dealer for exact number.	B6710
		Single row track floor only both sides	B6720
		Single row track floor right side only	B6730
		Single row track floor left side only	B6740
WHEELCHAIR SECUREMENTS (L-TRACK)		None	
		Sure-Lok 700 Series Kit (Includes 4 Retractors and Occupant Restraint System). State quantity of wheel chair stations For use w/L-Track. This option requires an in-floor track system. See option B6710	B6800
		Sure-Lok 800 Series Kit (Includes 4 Retractors and Occupant Restraint System) for use with WC 19 wheel chairs. State quantity of wheel chair stations. For use w/L-Track. This option requires an in-floor track system. See option B6710	B6810X
		Q-Straint QRT Deluxe Kit (Includes 4 Retractors and Occupant Restraint System). State quantity of wheel chair stations. For use w/L-Track. See option B6710	B6840
		Q-Straint QRT 360 Kit (Includes 4 Retractors and Occupant Restraint System) for use with WC 19 wheel chairs. State quantity of wheel chair stations For use w/L-Track. This option requires an in-floor track system. See option B6710	B6850

Product Category		Bus: A with Ford Transit	
WHEELCHAIR LOCATION	None		
	Dedicated wheel chair locations (qty). No seats, seat tracks or securements included.	B6860	
WHEELCHAIR SEC. STORAGE POUCH	A mounted storage device for the Wheelchair Tie Down & Occupant Restraint System (WTORS) SHALL BE PROVIDED for each wheel chair position. Storage device shall comply with National Standards.		
EVAC-AID	None		
	Add evac-aid fire blankets (quantity)	B6950	
FIRE BLANKET	None		
	Add fire blankets (state quantity)	B6960	
RADIO 2-WAY	None. Contact dealer for options		
PREWIRE FOR 2-WAY RADIO	None		
	Prewire for 2-way radio. Wiring to include for battery power, ground & ignition connections	B7030	
SURVEILLANCE CAMERA SYSTEM	None included but optional systems must include event marker. Contact Dealer for hardware availability and pricing if Camera System is desired. Pricing for labor and pre-wire is listed below.		
	Labor to install single camera system	B7710	
	Labor to install dual camera system	B7720	
	Labor to install three-camera system	B7730	
	Labor to install four-camera system	B7740	
MULTIFUNCTION BUS OPTION	None		
	Change bus to Activity Bus. To include all changes needed to convert bus into a white colored multi-function activity school bus, removes 8-way lamps, stop arm and yellow reflective is replaced with white reflective.	B8000	
ACTIVITY BUS COLOR OPTION	White		
	Custom Color Solid	B8050	
ACTIVITY; TRIM COLOR BUMPERS	Black front and rear		
	Custom color on bumpers	B8070	
ACTIVITY BUS GRILLE COLOR	Oem Standard		
ACTIVITY BUS RUB RAIL COLOR	White-only if custom bus color selected		
	Contrasting Color (quantity of rails). Select number of rails to have painted contrasting color	B8100	
GRAPHIC PACKAGE	None. Contact dealer for options		
WHITE LETTERING & TRIM	None		
	Upgrade white reflective package to sides & rear of unit for activity buses only.	B8190	
SEATING; ACTIVITY PASSENGER	None		
	Activity seats (state quantity). Manufacturer standard vinyl fireblock high back split seat. Must not recline.	B8200	
	Freedman seating (state quantity). Activity high back vinyl fireblock seats. Must not recline.	B8205	
	3-point activity seats. (state quantity)	B8210	

Product Category		Bus: A with Ford Transit	
		Freedman seating. 3-point. (state quantity)	B8215
SEATING; ACTIVITY PASSENGER UPHOLSTERY		Vinyl fireblock	
SEATING PASSENGER ARMREST		None	
		Add armrest (qty)	B8250
STORAGE; REAR EQUIPMENT		None	
		Add maximum rear equipment storage.	B8300
		Add small rear equipment stroage	B8310
STORAGE, OVERHEAD (INTERIOR LUGGAGE RACK)		None included. If selected, must be enclosed to meet national standards.	
		Add overhead parcel racks for activity bus	B8350