

Product Category		Bus: Low Floor FWD Ram	
Category Description	Base Spec and Description	Option	
Chassis Options			
AIR CLEANER (ENGINE)	Manufacturer Standard.		
ALTERNATOR	Manufacturer standard 220 amp		
AXLE, FRONT: MINIMUM LOAD	Maximum 4629 lbs		
AXLE, REAR: MINIMUM LOAD	Maximum 5291		
	GVWR Total 9,900lbs for single axle only.		
	3 point seat belts are standard.		
AXLE, REAR GEAR DIFFERENTIAL	Manufacturer Standard		
BATTERIES	Manufacturer Standard -Shall comply with National Standard.		
BRAKES, ABS, HYDRAULIC DISC FRONT AND REAR	Standard-Must meet Section 257.1813 of Section 13 of PA187 of 1990. ABS to meet FMVSS #121.		
BRAKES, PARKING	Shall comply National Standards and FMVSS.		
BUMPER, FRONT	Shall comply with National Standards. Bumper		
	Add 6 in. yellow numbers on bumper (state qty)		C1590
CHASSIS	Ram Promaster		
CIRCUIT BREAKERS	Shall comply with National Standards and FMVSS.		
COOLANT RECOVERY (ENGINE)	Must include some means for visual or electronic checking of coolant level without removing tank cap or releasing pressure from cooling system. All hoses shall be heavy duty rubber material.		
CRUISE CONTROL	None		
	Add cruise control		C1630
CLIPBOARD HOLDER	None		
	Add clipboard holder in drivers area		C1650
DOGHOUSE	See Insulation section. Base Spec: chassis shall include heat and noise insulation inside bus covering dash panel (firewall) area at least down to the point that body connects including engine cover (doghouse), which may be insulated on interior or exterior		
DRIVESHAFT GUARDS & SHIELDS	Shall comply with National Standards.		
ENGINE	Gasoline, minimum 3.6 L V-6; provide power curve to include horsepower, RPMs, torque, and fuel economy. Complete engine specifications and warranty information required.		
ENGINE SOUND DEADENING PACKAGE	Required in engine compartment, hood and firewall. Interior sound level shall comply with National Standards		
EXHAUST SYSTEM	Must exit at rear bumper.		
FIRE SUPPRESSION SYSTEM	None - Engine Compartment		
	DRY CHEMICAL SYSTEM - to be located in the engine compartment and be automatically activated when the fire detector has sensed a fire in the engine compartment. The system must also include a mechanism for activation by the driver. Include a lamp or buzzer to alert the driver when the system has been activated.		C2360

Product Category		Bus: Low Floor FWD Ram
	WATER/FOAM SYSTEM - to be located in the engine compartment and be automatically activated when the fire detector has sensed a fire in the engine compartment. The system must also include a mechanism for activation by the driver. Include a lamp or buzzer to alert the driver when the system has been activated.	C2365
FRAME SIDE MEMBERS	Must comply with National Standards and FMVSS	
FUEL TANK	Manufacturer Standard-24 gallon minimum. Must comply with National Standards and FMVSS.	
FULL INSTRUMENTATION PACKAGE (ENGINE)	Shall comply with National Standards, and all gauges shall be in English-no Metric.	
FOG LIGHTS	None	
HEADLIGHTS	Add fog lights	C2440
	Shall comply with National Standards. Daytime running lamps (DRL) shall be provided.	
	Add Wig Wag flashing headlights	C2450
HEATER BLOCK, INTERNAL (ENGINE)	None	
	Add block heater	C2470
HORNS	Shall comply with National Standards.	
HOSES (ENGINE)	Shall comply with National Standards.	
IGNITION SWITCH (ENGINE)	Controlled running and shutdown shall require electrical current provided by the ignition switch in ON, RUN and ACCESSORY positions	
LINE-SET TICKET	Manufacturer shall include with delivery of vehicle a line-set ticket that will reflect all chassis components, GAWR for both front and rear axles and GVWR. Web based is acceptable	
PAINT & FINISH, EXTERIOR	Must be Polyurethane or equal and a 5-year warranty and must comply with National Standards.	
	Additional after factory undercoating	C2610
PAINT, WHEELS	All wheels shall be painted per National Standards	
	Paint wheel black	C2620
	Paint wheels trim color	C2630
	Paint wheels white	C2640
	Paint wheel gray	C2650
RIMS	Shall comply with National Standards.	
RUST PROOFING	Underbody and firewall to be fully insulated and undercoated with rust proofing compound, including the battery compartment.	
SHOCK ABSORBERS	Front and rear, heavy-duty double-acting, piston type that are adequate size and axle load for the axle capacity.	
STEERING	Factory installed heavy-duty power steering with tilt.	
SUSPENSION, AXLE FRONT	Manufacturer Standard	
SUSPENSION, AXLE REAR	Manufacturer Standard	
SWITCHES, IGNITION	Shall comply with National Standards.	
TIRE & RIM, SPARE	None Must be dealer negotiated	
	Add Steering Tire	C3031
	Add Mud/Snow Tire	C3032

Product Category		Bus: Low Floor FWD Ram	
	Add Rim		C3033
	Add Steering Tire with Rim		C3034
	Add Mud/Snow Tire with Rim		C3035
TIRES, TUBELESS RADIAL	LT225/75R16C All Season Radial. OEM		
TOW HOOKS	2 mounted to rear of frame		
TOW BAR	None		
TRANSMISSION, AUTOMATIC	6-speed, heavy duty cooling		
TRANSMISSION, OIL	Shall comply with National Standards		
TRANSMISSION, WARRANTY	Manufacturer Standard		
TURN SIGNALS	Shall comply with National Standard		
WARRANTY	Provide Manufacturer Standard		
WHEELBASE, GVWR	To be compatible with size of bus		
WIRING	Shall comply with National Standards. The wiring shall be arranged in circuits, as required, with each circuit protected by a fuse breaker or electronic protection device. See also Electrical Wiring		
OPTIONAL OR EXTENDED WARRANTY	Dealer Negotiated		
Body Options			
ACCESS/FRONT BULKHEAD COMPARTMENT	Largest overhead compartment access door available		
AIR CONDITIONING	None; When choosing air conditioning it may not be compatible with other options and it must be verified with vendor.		
	Minimum 55,000 BTU		B1040
	60,000 plus BTU - Dual Compressor tied with skirt mounted compressor		B1050
AIR CONDITIONING. IN WALL SYSTEM	Standard with AC option		
AIR CONDITIONING. ROOF TOP CONDENSER	Standard with AC option		
AIR COND. FRONT OR REAR MOUNT	Rear mount standard with AC option		
AISLE STRIPS	Shall comply with National Standards.		
	Stainless steel		B1410
	Vinyl		B1430
	Aluminum		B1450
BACK UP ALARM AND STICKER	Shall comply with National Standards.		
BATTERY SLIDE OUT TRAY	Manufacturer Standard		
BODY DATA PLATE	Will be mounted in a clearly visible location inside body stating seating capacity, year manufactured, etc.		
BODY MOUNTING	Per manufacturers standards and shall comply with National Standards.		
BUMPER, REAR	Shall comply with National Standards and shall be painted glossy black matching National Standard #595A - Color 17038.		
BUS LOCK UP SYSTEM	None		
	Back only		B1550
BODY LOCKS KEYED ALIKE	Shall comply with National Standards.		
	Body locks keyed alike (state quantity)		B1650
BUZZERS/AUDIBLE SIGNAL/ALARMS	Shall comply with National Standards. See Doors and Windows sections for additional information.		
CROSSING GATE ARM	None		
	electric crossing gate arm		B1810
CROSSING GATE ARM INTERRUPT SWITCH	None		
	Add crossing gate arm interrupt switch		B1840

Product Category		Bus: Low Floor FWD Ram	
DEFOGGER FANS	None	Add 1 6 in. 2 speed defogger fan	B1920
DELIVERY, EXTENDED	Normal delivery upon manufacturers receipt of purchase order. For other delivery options contact dealer		
DOOR, ENTRANCE	Manufacturer Standard. Electric double swing out leaf design 34 x 76 inch. Door also serves as special service door with electric slide out ramp.		
DOOR ENTRANCE SWITCH	OEM standard-electric operated door		
ELECTRICAL EQUIPMENT & WIRING	Must meet SAE and National Standards. Shall be inside body channel readily accessible through removeable panels. All harnesses and wiring shall be protected from wall metal structure. All bodies shall be equipped with an electrical curcuit master switch and will cut body circuits "ON" and "OFF" by means of a master switch solenoid controlled by the ingnition switch (mounted in electrical compartment for aftermarket components only), controlled by ignition switch. See Wiring for additional information		
EXIT, EMERGENCY DOOR	All emergency exits shall conform to FMVSS #217 and all applicable State and Federal laws.		
EXIT, EMERGENCY DOOR, GLASS GUARD		Add glass guard on lower section of rear emergency door	B2155
EXIT, EMERGENCY WINDOW	All emergency exits shall conform to FMVSS #217 and all applicable State and Federal Laws.		
EXIT, ROOF HATCH	Transpec low profile model 197 Stardard. All emergency exits shall conform to FMVSS #217 and all applicable State and Federal Laws.		
		Deduct roof hatch	B2190
EXIT, ROOF HATCH, POWER VENT	None		
		Power vent for front or rear (state quantity)	B2310
ROOF VENT, STATIC	Shall comply with National Standards		
FENDERETTES	Rubber fenderettes standard		
FLOOR COVERING	Shall comply with National Standards		
		Colored floor and step treads. Please notify and verify availability of color of choice.	B2510
FLOOR: SUBFLOOR JOINTS SEALED	1 piece seamless plywood floor standard equipment.		
FLOOR COVERING ONE PIECE	See floor covering specification		
FUEL FILLER DOOR	None		
		Add door with latch	B2730
		Add door with lock	B2740
GLASS ENTRANCE DOOR	Safety glass upper and lower; shall comply with National Standards and FMVSS		
GRAB RAIL AT ENTRANCE	Stainless steel grab rail shall be provided at front entrance on left side securely mounted inside body close to bottom step for small children to reach and shall be designed to eliminate possibility of students clothing or personal items to become lodged or stuck upon exiting the bus		

Product Category		Bus: Low Floor FWD Ram	
HEADROOM	Add right side grab rail.		B2750
	Manufacturer Standard and shall comply with National Standards		
HEAT, BASEBOARD	None		
	Baseboard heat priced by body style w/access door for manual shut off		B2770
	Baseboard heat priced by body style w/automatic regulator valve		B2775
	Baseboard heat priced by foot w/access door for manual shut off (state qty)		B2780
	Baseboard heat priced by foot w/automatic regulator valve (state qty)		B2785
HEATER/DEFROSTERS	Suspended for full heating action, minimum output 40,000 BTU single fan output located to rear of wheelhouse, heater pipe to be covered. driver heater is OEM supplied. No silicone hosing		
HEATER, HOSES	Heater hoses shall be heavy duty and comply with National Standards. Contact dealer for other options, pricing, and availability.		
HEATER HOSE CLAMPS	Shall comply with National Standards.		
	Change to constant torque clamps		B3060
INSULATION	Shall comply with National Standards. Roof and side walls shall be fully insulated including body bow cavities. Each bidder shall supply complete information on insulation. Premium type of insulation with the body will be considered standard. Noise package should be a separate line item.		
LETTERING, IDENTIFICATION, & TRIM	Must meet State and National Standards. Lettering specifics provided by each school district. Reflective markings: must be reflective tape as follows: 1" tape outlining all exits. Each bus shall be numbered with numbers assigned by the school district and made of vinyl type. Numbers will be four locations where numbers will be placed (front, sides and rear) All lettering shall be 6". Reflective package: 2" tape below beltline on both sides, 1" tape completely outlining rear of bus from below cap to rear bumper, School Bus lettering front and rear.		
LETTERING; INTERIOR SEAT #'S	None		
	Add numbers for interior seats; 2" decal (state quantity)		B3120
LETTERING; ROOF TOP NUMBERS	None		
	Add 24 inch numbers (state qty of digits). Price is per digit		B3130
LICENSE PLATE HOLDER	Shall be on left rear outside of body with suitable method for mounting license plate		
LIGHT MONITOR, EXTERIOR LIGHTS	None		
	Light monitor system LED		B3290
	Light monitor system not LED		B3300
LIGHT, LANDING	Next to entrance door, outside skirt mounted		
	Delete landing light		B3310
	Change to LED type light		B3320
LIGHT, LED STEPWELL LAMP	None		

Product Category		Bus: Low Floor FWD Ram
LIGHT, STROBE	Add LED stepwell lamp Strobe light is required. Shall comply with State and National Standards.	B3360
LIGHTS	Add Brush guard Lighting system shall be Weldon 7000 transistorized flasher OR EQUAL OR MULTIPLEX control units and shall include turn signals, stop lights, marker lights, stepwell lights, parking lights, landing light, interior lights, and eight (8) light warning system. Rear directional signal, side directionals, stop lights, and back-up lights in addition to the regular stop lamps. All exterior lights shall be bulb and conform to National Standards. (8 way lights include 3" black band around)	B3430
	Change 8 way to strobing LED	B3460
	Change the tail, brake, turn and backups to LED style lamps	B3470
	Change 8 way, tail, brake, back up and turn to LED style lamps	B3480
LIGHTS, CLEARANCE	Recessed and LED are manufacturers standard. Must meet National Standards.	
LIGHT, EMERGENCY DOOR	None	
	Add Red ICC light over emergency door (state Quantity)	B3520
LIGHTS, INTERIOR	There shall be 4 LED dome lights installed to include 1 in drivers compartment and 3 in passenger compartment. The landing light shall be activated when the door opening mechanism is initiated.	
	Add maximum led dome lights Included	B3570
LIGHTS; INTERIOR DRIVER DOME	Delete drivers dome	B3580
LIGHTS TAIL TURN FLUSH MOUNT		
	Stop tail 4" flush mount LED	B3600
	Stop tail 4" flush mount incandescent	B3610
LIGHT VISORS	None	
	Individual visors for warning lights in lieu of visors that cover amber and red lights.	B3620
LOCKS, DOOR	Standard	
MIRRORS, CROSSOVER	Shall come equipped with two convex elliptical cross-view mirrors mounted on front of vehicle. Shall be heated. Contact dealer for options and pricing	
MIRRORS, SIDE	Body shall be equipped with two split - style-type side-view mirrors supported from top or bottom. Shall be heated. Contact dealer for options and pricing.	
	remote, heated	B3940
MIRRORS BRACKETS	Shall comply with National Standards.	
	Stainless steel brackets for crossover & side rearview mirrors	B3970
MIRROR, TIMER	None	
	Timer for heated mirror	B3990

Product Category		Bus: Low Floor FWD Ram	
MIRROR, INSIDE REAR-VIEW		A over head mirror mounted above driver and a glass mounted chassis OEM shall be included	
MUD FLAPS		2 rear attached appropriately and made of rubber material.	
NOISE REDUCTION SYSTEM		Include 1/2" sound abatement package in floor and firewall	
NOISE REDUCTION FIREWALL		Acoustical headliner full length of bus Included	B4070
PAINT & FINISH		Body shall be painted with polyurethane and according to specifications as set forth by the National Standards, which shall include all words, letters and numbers to meet those specifications.	
PAINT HOOD		Hood shall be painted NSBY yellow.	
		The flat top surface of the hood may be non-reflective black. Paint Hood Black.	
PAINT, ROOF		Roof shall be NSBY yellow.	
		Add painted white roof	B4210
PANELING, EXTERIOR		Side skirts between the front and rear axles shall extend down to within two inches plus or minus of the horizontal line from the center of the front spindle to the center of the rear axle on new unloaded bus on flat, level surface. Side skirt length may extend lower than this requirement. Exterior paneling includes sheet metal skin forming exterior surface of body and shall be 20-gauge aluminum minimum thickness and be attached to bow frames and strainers to act as an integral part of structural frame.	
PANELING, INTERIOR		Interior body shall be lined with panels securely fastened to adjoining parts. All joints are to be covered. No sharp edges will be left; molding shall be securely fastened so dirt will not readily work under it. Interior paneled areas immediately below window line shall be galvanized embossed steel, aluminum in color. Exposed edges shall be beaded, hemmed, flanged, or treated to eliminate sharp edges.	
PANEL, SHOULDER PAD		None	
		Full bus length	B4310
POWER SOURCE		Per OEM	
RADIO SYSTEM		AM/FM/CD	
		Add PA to radio	B4550
RADIO SYS. WITH EXT. PA & SPEAKER		None	
		Add exterior speaker	B4560
REFLECTORS		2 amber reflectors on each side of bus near the front and 2 red on rear side panels, 2 red on rear panels, and 2 amber intermediate on sides- Shall comply with FMVSS	
RUB RAILS		3 applied rub rails	
RUST PROOFING		Must be fully rust proofed including battery compartment, State Manufacturer Standard	

Product Category		Bus: Low Floor FWD Ram	
SAFETY EQUIPMENT		Per KAR (Kansas Administrative Regulation) 91-38-2. (1) Each school bus shall contain the following emergency supplies: (A) At least one 2A-10BC fire extinguisher; (B) at least one readily identifiable first aid kit in a removable, waterproof, and dustproof container; (C) at least one readily identifiable body fluid clean-up kit, in a removable, water proof, and dustproof container; (D) a minimum of three reflectorized triangle warning devices, securely stored but in an accessible location. (E) a minimum of one emergency seat belt cutter./ durable webbing cutter having a full widthhandgrip and a protected, replaceable or non-corrodible blade. The required webbing cutter shall be mounted in a location accessible to the seated driver in an easily detachable manner(2) The first aid kit, body fluid clean-up kit, and fire extinguisher shall be mounted in full view of, and readily accessible to, the driver.	
SEAT, DRIVER		Base Spec: shall be manufacturer standard with adjustable positiona and three point lab/shoulder seat belt.	
		Upgrade to cloth seat	B4770
SEAT, DRIVER; SEAT BELT		Seat belts for drivers with adjustable type shoulder harness are required.	
SEAT BARRIERS		Shall be equipped with the appropriate seat barriers to comply with the National Standards and FMVSS 222.	
SEATS, PASSENGER. NOTE: The school bus will be equipped with seats. The following are options.		Seats shall be supported with two-legged seat rail mounted inside the body. Padding for seats shall be as specified in National Standards Seats must meet National Standards. Minimum knee room spacing between the seats shall be 24". Fire block 42 oz. upholstery. DOT 45" high back seat.	
		Upgrade to 52 oz. upholstery	B5050
SEATS, FIRE BLOCK		Required	
SEATS, PASSENGER: COLOR		Shall comply with National Standards.	
		Color other than manufacturer standard. Please notify and verify availability of color of choice.	B5090
SEATS, DEDUCT FOR SEATS REMOVED		None	
SEAT BELT - Lap belts shall not be installed on passenger seats in large school buses (over 10,000 pounds GVWR) except in conjunction with child safety restraint systems that comply with the requirements of FMVSS No. 213, Child Restraint Systems.		3 point lap shoulder standard equipment.	
SEATS, 3 POINT, 36" FLOOR MOUNT - includes 2 point lap/shoulder belt			
		36 inch seat (state quantity)	B5440
STORAGE POUCH KICK PANEL BARRIER		None (located behind driver on barrier)	

Product Category		Bus: Low Floor FWD Ram	
		Single pouch barrier	B5750
		Five pouch barrier	B5770
KICK PANEL		One on right side	
		Add additional left side front	B5780
STEP; DRIVER		None	
		Add Running board type step full width	B5790
STEPWELL		Stepwell shall be of non - corrosive steel, all screws and bolts shall be non corrosive steel, and shall meet National Standards. It shall contain at least one light. Step shall be covered with rubberized flooring step tread.	
STOP ARM SIGNAL		Single electric incandescent arm shall be considered standard equipment. Stop arm shall be constructed of metal ribbed or reinforced panel; such stop arm shall include wind guard and be equipped with two alternating red flashing lights. Stop arm shall meet National Standards and FMVSS #131.	
		Electric LED cluster	B5910
		Electric LED strobing	B5920
		Electric LED on STOP	B5930
STORAGE COMPARTMENT DRIVER ABOVE DRIVER		Included Standard Equipment	
STUDENT REMINDER SYSTEM		Included. Manufacturer Standard to be triggered by warning lights	
		Delete Student Reminder System	B6080
STUDENT REMINDER ACTIVATION			
		To be armed by ignition.	B6110
		To be armed by other methods	B6120
SUNSHADE/SUNSHIELD		Shall comply with National Standards.	
VENTILATION		Shall comply with National Standards	
WINDOW, STORM SASH, DRIVER SIDE		None (not tinted)	
		Add window, left side, storm sash (state quantity)	B6220
WINDOW, STORM SASH, ENTRANCE DOOR		None	
		Storm sash, upper only	B6230
		Storm sash whole door	B6240
WINDOW, STORM SASH, PASSENGER		None (not tinted)	
		Add passenger side windows, storm sash. (state quantity)	B6250
WINDOW, REAR		Manufacturer Standard	
		Tempered, Clear	B6260
		Laminated, tinted	B6270
WINDOWS		Windows shall be single pane split type construction safety glass to set in aluminum or steel frame. Emergency windows shall meet state specifications and National Rule 217. Windshield, service and emerg doors, side and rear windows may be equipped with max integral tinting allowed by fed, state, or ANSI standards for respective locations, except that windows rear of drivers compartment, if tinted, shall have approx 28% light transmission. Inside windows shall have marks indicating the half way point.	
		Remove tint	B6310
		Laminated, tinted	B6320
		Laminated, clear	B6330
WINDOW, SIDE SASHES		Shall comply with National Standards.	

Product Category		Bus: Low Floor FWD Ram	
WINDSHIELD		Windshield to be OEM standard.	
WINDSHIELD WASHER		Windshield washer fluid container is to be OEM Standard and must meet State and National Standards. Reservoir shall be full upon delivery to owner and protected to 20°F below zero	
WIPER BLADES		Wipers are to be electrical, intermittent, wet arm and 2-speed. Wipers shall comply with FMVSS #104	
FLOOR TRACKING SYSTEM (NO SECUREMENTS)		None	
		4 floor rows/1 row over window/L-track. Includes 4 floor rows, 1 row over windows, L-track. State quantity of wheelchair placements. SecUREMENTS or seats not included. When choosing floor tracking systems, you will need to deduct seats. Deduct approximately 2 seats per wheelchair station. Check with dealer for exact number.	B6710
WHEELCHAIR SECUREMENTS (L-TRACK)		None	
		Sure-Lok 700 Series Kit (Includes 4 Retractors and Occupant Restraint System). State quantity of wheel chair stations For use w/L-Track. This option requires an in-floor track system. See option B6710	B6800
		Sure-Lok 800 Series Kit (Includes 4 Retractors and Occupant Restraint System) for use with WC 19 wheel chairs. State quantity of wheel chair stations. For use w/L-Track. This option requires an in-floor track system. See option B6710	B6810
		Q-Straint QRT Deluxe Kit (Includes 4 Retractors and Occupant Restraint System). State quantity of wheel chair stations. For use w/L-Track. See option B6710	B6840
		Q-Straint QRT 360 Kit (Includes 4 Retractors and Occupant Restraint System) for use with WC 19 wheel chairs. State quantity of wheel chair stations For use w/L-Track. This option requires an in-floor track system. See option B6710	B6850
WHEELCHAIR LOCATION		None	
		Dedicated wheel chair locations (qty). No seats, seat tracks or secUREMENTS included.	B6860
WHEELCHAIR SEC. STORAGE POUCH		A mounted storage device for the Wheelchair Tie Down & Occupant Restraint System (WTORS) SHALL BE PROVIDED for each wheel chair position. Storage device shall comply with National Standards.	
EVAC-AID		None	
		Add evac-aid fire blankets (quantity)	B6950
FIRE BLANKET		None	
		Add fire blankets (state quantity)	B6960
RADIO 2-WAY		None. Contact dealer for options	
		2-way radio. Please check with vendor for a quote as there are numerous manufacturers and options available.	B7020

Product Category		Bus: Low Floor FWD Ram	
PREWIRE FOR 2-WAY RADIO	None	Prewire for 2-way radio. Wiring to include for battery power, ground & ignition connections	B7030
SURVEILLANCE CAMERA SYSTEM	None included but optional systems must include event marker. Contact Dealer for hardware availability and pricing if Camera System is desired. Pricing for labor and pre-wire is listed below.		
		Labor to install single camera system	B7710
		Labor to install dual camera system	B7720
		Labor to install three-camera system	B7730
		Labor to install four-camera system	B7740
MULTIFUNCTION BUS OPTION	None	Change bus to Activity Bus. To include all changes needed to convert bus into a white colored multi-function activity school bus, removes 8-way lamps, stop arm and yellow reflective is replaced with white reflective.	B8000
ACTIVITY BUS COLOR OPTION	White	Custom Color Solid	B8050
ACTIVITY; TRIM COLOR BUMPERS	Black front and rear	Custom color on bumpers	B8070
ACTIVITY BUS GRILLE COLOR	Oem Standard		
ACTIVITY BUS RUB RAIL COLOR	White-only if custom bus color selected	Contrasting Color (quantity of rails). Select number of rails to have painted contrasting color	B8100
WHITE LETTERING & TRIM	None	Upgrade white reflective package to sides & rear of unit for activity buses only.	B8190