

Product Category	Bus: A and AII	
Category Description	Base Spec and Description	Option
<b>Chassis Options</b>		
<b>AIR CLEANER (ENGINE)</b>	<b>Manufacturer Standard.</b>	
<b>ALTERNATOR</b>	<b>Manufacturer standard</b>	
	Upgrade alternator	C1120
<b>AXLE, FRONT: MINIMUM LOAD</b>	<b>By capacity. Minimum 4,300 lbs ; 4,100 lbs for single rear wheel.</b>	
<b>AXLE, REAR: MINIMUM LOAD</b>	<b>By capacity. GVWR Total 9,900lbs for single rear wheel and 12,300 for dual rear wheel.</b>	
	10,000 lbs. 3 point seat belts are required for this option	C1270
	14,200 lbs GM/Chev	C1290
	14,500 lbs Ford Must select C167 or C168	C1300
<b>AXLE, REAR GEAR DIFFERENTIAL</b>	<b>Manufacturer Standard</b>	
<b>BATTERIES</b>	<b>Shall comply with National Standard. Standard equipment is gas engine with dual 610 CCA batteries.</b>	
<b>BATTERY CUT OFF SWITCH</b>		
<b>BRAKES, ABS, HYDRAULIC DISC FRONT AND REAR</b>	<b>Standard-Must meet Section 257.1813 of Section 13 of PA187 of 1990. ABS to meet FMVSS #121.</b>	
<b>BRAKES, PARKING</b>	<b>Shall comply with State and National Standards.</b>	
<b>BUMPER, FRONT</b>	<b>Shall comply with National Standards. Bumper shall be painted black.</b>	
	Add 6 in. yellow numbers on bumper (state qty)	C1590
<b>CHASSIS</b>	<b>Chevrolet/GMC</b>	
<b>CIRCUIT BREAKERS</b>	<b>Shall comply with National Standards and State Specifications</b>	
<b>CRUISE CONTROL</b>	<b>None</b>	
	Add cruise control	C1630
<b>CLIPBOARD HOLDER</b>	<b>None</b>	
	Add clipboard holder in drivers area	C1650
<b>DOGHOUSE</b>	<b>See Insulation section. Base Spec: chassis shall include heat and noise insulation inside bus covering dash panel (firewall) area at least down to the point that body connects including engine cover (doghouse), which may be insulated on interior or exterior</b>	
<b>DRIVESHAFT GUARDS &amp; SHIELDS</b>	<b>Shall comply with National Standards.</b>	
<b>ENGINE</b>	<b>Gasoline, minimum 6.0 L; provide power curve to include horsepower, RPMs, torque, and fuel economy. Complete engine specifications and warranty information required.</b>	
	Chevrolet CNG engine	C1660
	Ford CNG engine	C1670
	Propane engine	C1680
	Ford Gasoline V8 engine	C1710
	Ford Gasoline V10 engine	C1720
	Convert to Hybrid/Electric vehicle	C1770

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>ENGINE/EXHAUST BRAKE</b>	<b>None - contact dealer for price and availability - online has this comment. Should it be on the A or removed?</b>	
<b>ENGINE SOUND DEADENING PACKAGE</b>	<b>Required in engine compartment, hood and firewall. Interior sound level shall comply with National Standards</b>	
<b>EXHAUST SYSTEM</b>	<b>Must exit at rear bumper.</b>	
<b>FIRE SUPPRESSION SYSTEM</b>	<b>None - Engine Compartment</b>	
	DRY CHEMICAL SYSTEM - to be located in the engine compartment and be automatically activated when the fire detector has sensed a fire in the engine compartment. The system must also include a mechanism for activation by the driver. Include a lamp or buzzer to alert the driver when the system has been activated.	C2360
	WATER/FOAM SYSTEM - to be located in the engine compartment and be automatically activated when the fire detector has sensed a fire in the engine compartment. The system must also include a mechanism for activation by the driver. Include a lamp or buzzer to alert the driver when the system has been activated.	C2365
<b>FRAME SIDE MEMBERS</b>	<b>Must comply with National Standards</b>	
<b>FUEL TANK</b>	<b>Manufacturer Standard-30 gallon minimum. Must comply with National Standards.</b>	
<b>FULL INSTRUMENTATION PACKAGE (ENGINE)</b>	<b>Shall comply with National Standards, and all gauges shall be in English-no Metric.</b>	
<b>FOG LIGHTS</b>	<b>None</b>	
	Add fog lights	C2440
<b>HEADLIGHTS</b>	<b>Shall comply with National Standards. Daytime running lamps (DRL) shall be provided.</b>	
<b>HEATER BLOCK, INTERNAL (ENGINE)</b>	<b>None</b>	
	Add block heater	C2470
<b>HOOD</b>		
<b>HORNS</b>	<b>Shall comply with National Standards.</b>	
<b>HOSES (ENGINE)</b>	<b>Shall comply with National Standards.</b>	
<b>HOSE CLAMPS</b>		
<b>IGNITION SWITCH (ENGINE)</b>	<b>Controlled running and shutdown shall require electrical current provided by the ignition switch in ON, RUN and ACCESSORY positions</b>	
<b>LINE-SET TICKET</b>	<b>Manufacturer shall include with delivery of vehicle a line-set ticket that will reflect all chassis components, GAWR for both front and rear axles and GVWR. Web based is acceptable</b>	
<b>PAINT &amp; FINISH, EXTERIOR</b>	<b>Must be Polyurethane or equal and a 5-year warranty and must comply with National Standards.</b>	
	Additional after factory undercoating	C2610
<b>PAINT, WHEELS</b>	<b>All wheels shall be painted per National Standards</b>	

<b>Product Category</b>	<b>Bus: A and AII</b>	
	Paint wheel black	C2620
	Paint wheels white	C2640
	Paint wheel gray	C2650
<b>RIMS</b>	<b>Shall comply with National Standards.</b>	
<b>RUST PROOFING</b>	<b>Underbody and firewall to be fully insulated and undercoated with rust proofing compound, including the battery compartment.</b>	
<b>SHOCK ABSORBERS</b>	<b>Front and rear, heavy-duty double-acting, piston type that are adequate size and axle load for the axle capacity.</b>	
<b>STEERING</b>	<b>Factory installed heavy-duty power steering with tilt.</b>	
<b>SUSPENSION, AXLE FRONT</b>	<b>Manufacturer Standard</b>	
<b>SUSPENSION, AXLE REAR</b>	<b>Manufacturer Standard</b>	
<b>SWITCHES, IGNITION</b>	<b>Shall comply with National Standards.</b>	
<b>TIRE &amp; RIM, SPARE</b>	<b>None Must be dealer negotiated</b>	
<b>TIRES, TUBELESS RADIAL</b>	<b>LT225/75R16E All Season Radial. OEM</b>	
<b>TOW HOOKS</b>	<b>2 mounted to rear of frame</b>	
<b>TOW BAR</b>	<b>None</b>	
<b>TRANSMISSION, AUTOMATIC</b>	<b>6-speed, heavy duty cooling</b>	
<b>TRANSMISSION, OIL</b>	<b>Shall comply with National Standards</b>	
<b>TRANSMISSION, WARRANTY</b>	<b>Shall comply with National Standards</b>	
<b>TURN SIGNALS</b>	<b>Shall comply with National Standards.</b>	
<b>WARRANTY</b>	<b>Provide Manufacturer Standard.</b>	
<b>WHEELBASE, GVWR</b>	<b>To be compatible with size of bus</b>	
<b>WIRING</b>	<b>Shall comply with National Standards. The wiring shall be arranged in circuits, as required, with each circuit protected by a fuse breaker or electronic protection device. See also Electrical Wiring</b>	
<b>OPTIONAL OR EXTENDED WARRANTY</b>	<b>Dealer Negotiated</b>	
<b>Body Options</b>		
<b>ACCESS/FRONT BULKHEAD COMPARTMENT</b>	<b>Largest overhead compartment access door available</b>	
<b>AIR CONDITIONING</b>	<b>None; When choosing air conditioning it may not be compatible with other options and it must be verified with vendor.</b>	
	Minimum 45,000 BTU	B1030
	Minimum 55,000 BTU	B1040
	60,000 plus BTU - Dual Compressor tied with skirt mounted compressor	B1050
<b>AIR CONDITIONING. IN WALL SYSTEM</b>	<b>None</b>	
	Add in wall recessed system	B1350
<b>AIR CONDITIONING. ROOF TOP CONDENSER</b>	<b>None</b>	
	Add roof top condenser for air conditioning	B1360
<b>AISLE STRIPS</b>	<b>Shall comply with National Standards.</b>	
	Stainless steel	B1410
	Vinyl	B1430
	Deduct aisle strips	B1440
	Aluminum	B1450
<b>BACK UP ALARM AND STICKER</b>	<b>Shall comply with National Standards.</b>	
<b>BATTERY SLIDE OUT TRAY</b>	<b>None</b>	
	Add battery box	B1520

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>BODY DATA PLATE</b>	Will be mounted in a clearly visible location inside body stating seating capacity, year manufactured, etc.	
<b>BODY MOUNTING</b>	Per manufacturers standards and shall comply with National Standards.	
<b>BUMPER, REAR</b>	Shall comply with National Standards and shall be painted glossy black matching National Standard #595A - Color 17038.	
<b>BUS LOCK UP SYSTEM</b>	None	
	Back only	B1550
<b>BODY LOCKS KEYED ALIKE</b>	Shall comply with National Standards.	
<b>BUZZERS/AUDIBLE SIGNAL/ALARMS</b>	Shall comply with National Standards. See Doors and Windows sections for additional information.	
<b>CROSSING GATE ARM</b>	None	
	electric crossing gate arm	B1810
<b>CROSSING GATE ARM INTERRUPT SWITCH</b>	None	
	Add crossing gate arm interrupt switch	B1840
<b>DEFOGGER FANS</b>	None	
	Add 1 6 in. 2 speed defogger fan	B1920
<b>DELIVERY, EXTENDED</b>	Normal delivery upon manufacturers receipt of purchase order. For other delivery options contact dealer	
<b>DOOR, ENTRANCE</b>	Entrance Door, passenger. Base Spec: Shall be manual, double-out split-type located at right front of bus with padded header over entrance door. Double bearing chromium plated mechanical control shall be mounted within comfortable reach of the driver and meet National Standards.	
	Electric, double out, split type	B1980
<b>DOOR ENTRANCE SWITCH</b>	OEM standard-electric operated door	
<b>ELECTRICAL EQUIPMENT &amp; WIRING</b>	Must meet SAE and National Standards. Shall be inside body channel readily accessible through removeable panels. All harnesses and wiring shall be protected from wall metal structure. All bodies shall be equipped with an electrical curcuit master switch and will cut body circuits "ON" and "OFF" by means of a master switch solenoid controlled by the ignition switch (mounted in electrical compartment for aftermarket components only), controlled by ignition switch. See Wiring for additional information	
<b>EXIT, EMERGENCY DOOR</b>	All emergency exits shall conform to FMVSS #217 and all applicable State and Federal laws.	
<b>EXIT, EMERGENCY DOOR, GLASS GUARD</b>		
	Emergency window	B2160
<b>EXIT, EMERGENCY WINDOW</b>	All emergency exits shall conform to FMVSS #217 and all applicable State and Federal Laws.	
	Deduct window for under 10,000# GVW	B2165

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>EXIT, ROOF HATCH</b>	<b>All emergency exits shall conform to FMVSS #217 and all applicable State and Federal Laws.</b>	
	Deduct roof hatch	B2190
	Transpec (state qty)	B2250
<b>EXIT, ROOF HATCH, POWER VENT</b>	<b>None</b>	
	Power vent for front or rear (state quantity)	B2310
<b>ROOF VENT, STATIC</b>	<b>Shall comply with National Standards</b>	
<b>FENDERETTES</b>	<b>None</b>	
	Rubber fenderettes	B2350
<b>FLOOR COVERING</b>	<b>Shall comply with National Standards</b>	
	Colored floor and step treads. Please notify and verify availability of color of choice.	B2510
<b>FLOOR: SUBFLOOR PLYWOOD</b>	<b>Floor shall be 1/2" exterior grade treated plywood</b>	
	1/2" marine grade plywood	B2540
	5/8" marine grade plywood	B2541
<b>FLOOR: SUBFLOOR JOINTS SEALED</b>	<b>Base Spec: None</b>	
	All subfloor joints water proof sealed	B2550
<b>FLOOR COVERING ONE PIECE</b>	<b>See floor covering spec</b>	
	Add door with latch	B2730
	Add door with lock	B2740
<b>GLASS ENTRANCE DOOR</b>	<b>Safety glass upper and lower; shall comply with National Standards and FMVSS</b>	
<b>GRAB RAIL AT ENTRANCE</b>	<b>Stainless steel grab rail shall be provided at front entrance on left side securely mounted inside body close to bottom step for small children to reach and shall be designed to eliminate possibility of students clothing or personal items to become lodged or stuck upon exiting the bus</b>	
	Add right side grab rail.	B2750
<b>HEADROOM</b>	<b>Minimum 73" headroom; Minimum 69" on single rear wheel</b>	
	73 inch headroom for single rear wheel	B2800
<b>HEAT, BASEBOARD</b>	<b>None. Contact dealer for options</b>	
<b>HEATER/DEFROSTERS</b>	<b>Suspended for full heating action, minimum output 40,000 BTU single fan output located to rear of wheelhouse, heater pipe to be covered. driver heater is OEM supplied. No silicone hosing</b>	
	Add heater booster pump	B2870
<b>HEATER, HOSES</b>	<b>Heater hoses shall be heavy duty and comply with National Standards. Contact dealer for other options, pricing, and availability.</b>	
<b>HEATER HOSE CLAMPS</b>	<b>Shall comply with National Standards.</b>	
	Change to constant torque clamps	B3060
<b>INSULATION</b>	<b>Shall comply with National Standards. Roof and side walls shall be fully insulated including body bow cavities. Each bidder shall supply complete information on insulation. Premium type of insulation with the body will be considered standard. Noise package should be a separate line item.</b>	
<b>ILLUMINATED SCHOOL BUS SIGN FRONT AND REAR</b>	<b>None</b>	

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>LETTERING, IDENTIFICATION, &amp; TRIM</b>	<b>Must meet State and National Standards. Lettering specifics provided by each school district. Reflective markings: must be reflective tape as follows: 1" tape outlining all exits. Each bus shall be numbered with numbers assigned by the school district and made of vinyl type. Numbers will be four locations where numbers will be placed (front, sides and rear) All lettering shall be 6". Reflective package: 2" tape below beltline on both sides, 1" tape completely outlining rear of bus from below cap to rear bumper, School Bus lettering front and rear.</b>	
	3M brand tape	B3100
	Reflexite brand tape	B3110
<b>LETTERING; INTERIOR SEAT #'S</b>	<b>None</b> Add numbers for interior seats; 2" decal (state quantity)	B3120
<b>LETTERING; ROOF TOP NUMBERS</b>	<b>None</b>	
	Add 24 inch numbers (state qty of digits). Price is per digit	B3130
<b>LICENSE PLATE HOLDER</b>	<b>Shall be on left rear outside of body with suitable method for mounting license plate</b>	
<b>LIGHT MONITOR, EXTERIOR LIGHTS</b>	<b>None</b>	
	Light monitor system LED	B3290
	Light monitor system not LED	B3300
<b>LIGHT, LANDING</b>	<b>Next to entrance door, outside skirt mounted</b>	
	Delete landing light	B3310
	Change to LED type light	B3320
<b>LIGHT, LED STEPWELL LAMP</b>	<b>None</b>	
	Add LED stepwell lamp	B3360
<b>LIGHT, STROBE</b>	<b>Strobe light is required. Shall comply with State and National Standards.</b>	
	Add Brush guard	B3430
<b>LIGHTS</b>	<b>Lighting system shall be Weldon 7000 transistorized flasher OR EQUAL OR MULTIPLEX control units and shall include turn signals, stop lights, marker lights, stepwell lights, parking lights, landing light, interior lights, and eight (8) light warning system. Rear directional signal, side directionals, stop lights, and back-up lights in addition to the regular stop lamps. All exterior lights shall be bulb and conform to National Standards. (8 way lights include 3" black band around)</b>	
	Change 8 way to strobing LED	B3460
	Change the tail, brake, turn and backups to LED style lamps	B3470
	Change 8 way, tail, brake, back up and turn to LED style lamps	B3480

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>LIGHTS, CLEARANCE</b>	<b>Manufacturers standard clearance lights and must meet State and National Standards.</b>	
	Add armored marker	B3490
	Change to LED style	B3500
	Add armored marker and add LED style	B3510
<b>LIGHT, EMERGENCY DOOR</b>	<b>None</b>	
	Add Red ICC light over emergency door (state Quantity)	B3520
<b>LIGHTS, INTERIOR</b>	<b>There shall be 4 dome lights installed to include 1 in drivers compartment and 3 in passenger compartment. The landing light shall be activated when the door opening mechanism is initiated.</b>	
	LED Dome lights	B3530
	Add maximum dome lights	B3560
	Add maximum led dome lights	B3570
<b>LIGHTS; INTERIOR DRIVER DOME</b>	<b>Included</b>	
	Delete drivers dome	B3580
<b>LIGHTS TAIL TURN FLUSH MOUNT</b>		
	Stop tail 4" flush mount LED	B3600
	Stop tail 4" flush mount incandescent	B3610
<b>LIGHT VISORS</b>	<b>None</b>	
	Individual visors for warning lights in lieu of visors that cover amber and red lights.	B3620
	Dual light visors for warning lights	B3630
<b>LOCKS, DOOR</b>	<b>Standard</b>	
	Delete	B3635
<b>MIRRORS, CROSSOVER</b>	<b>Shall come equipped with two convex elliptical cross-view mirrors mounted on front of vehicle. Shall be heated. Contact dealer for options and pricing</b>	
<b>MIRRORS, SIDE</b>	<b>Body shall be equipped with two split - style-type side-view mirrors supported from top or bottom. Shall be heated. Contact dealer for options and pricing.</b>	
	remote, heated	B3940
<b>MIRRORS BRACKETS</b>	<b>Shall comply with National Standards.</b>	
<b>MIRROR, TIMER</b>	<b>None</b>	
	Timer for heated mirror	B3990
<b>MIRROR, INSIDE REAR-VIEW</b>	<b>A over head mirror mounted above driver and a glass mounted chassis oem shall be included</b>	
<b>MUD FLAPS</b>	<b>2 rear attached appropriately and made of rubber material.</b>	
<b>NOISE REDUCTION SYSTEM</b>	<b>Include 1/2" sound abatement package in floor and firewall</b>	
	Acoustical headliner full length of bus	B4070
<b>NOISE REDUCTION FIREWALL</b>	<b>Included</b>	
<b>PAINT &amp; FINISH</b>	<b>Body shall be painted with polyurethane and according to specifications as set forth by the National Standards, which shall include all words, letters and numbers to meet those specifications.</b>	
<b>PAINT HOOD</b>	<b>Hood shall be painted NSBY yellow.</b>	

<b>Product Category</b>	<b>Bus: A and AII</b>	
	The flat top surface of the hood may be non-reflective black. Paint Hood Black.	
<b>PAINT, ROOF PANELING, EXTERIOR</b>	<b>Roof shall be white.</b> Side skirts between the front and rear axles shall extend down to within two inches plus or minus of the horizontal line from the center of the front spindle to the center of the rear axle on new unloaded bus on flat, level surface. Side skirt length may extend lower than this requirement. Exterior paneling includes sheet metal skin forming exterior surface of body and shall be 20-gauge steel minimum thickness and be attached to bow frames and strainers to act as an integral part of structural frame.	
	Optional 16 ga. exterior metal Aluminum panels	B4250 B4260
<b>PANELING, INTERIOR</b>	<b>Interior body shall be lined with panels securely fastened to adjoining parts. All joints are to be covered. No sharp edges will be left; molding shall be securely fastened so dirt will not readily work under it. Interior paneled areas immediately below window line shall be galvanized embossed steel, aluminum in color. Exposed edges shall be beaded, hemmed, flanged, or treated to eliminate sharp edges.</b>	
<b>PANEL, SHOULDER PAD</b>	<b>None</b> Full bus length	B4310
<b>POWER SOURCE RADIO SYSTEM</b>	<b>Per OEM</b> <b>AM/FM/CD</b>	
	Downgrade to PA only Add PA to radio	B4520 B4550
<b>RADIO SYS. WITH EXT. PA &amp; SPEAKER</b>	<b>None</b> Add exterior speaker	B4560
<b>REFLECTORS</b>	<b>2 amber reflectors on each side of bus near the front and 2 red on rear side panels, 2 red on rear panels, and 2 amber intermediate on sides- Shall comply with FMVSS</b>	
<b>RUB RAILS</b>	<b>3 applied rub rails</b> Add fourth rub rail	B4610
<b>RUST PROOFING</b>	<b>Must be fully rust proofed including battery compartment, State Manufacturer Standard</b>	



Product Category	Bus: A and AII	
<b>SAFETY EQUIPMENT</b>	Per KAR (Kansas Administrative Regulation) 91-38-2. (1) Each school bus shall contain the following emergency supplies: (A) At least one 2A-10BC fire extinguisher; (B) at least one readily identifiable first aid kit in a removable, waterproof, and dustproof container; (C) at least one readily identifiable body fluid clean-up kit, in a removable, water proof, and dustproof container; (D) a minimum of three reflectorized triangle warning devices, securely stored but in an accessible location. (E) a minimum of one emergency seat belt cutter./ durable webbing cutter having a full widthhandgrip and a protected, replaceable or non-corrodible blade. The required webbing cutter shall be mounted in a location accessible to the seated driver in an easily detachable manner(2) The first aid kit, body fluid clean-up kit, and fire extinguisher shall be mounted in full view of, and readily accessible to, the driver.	
<b>SEAT, DRIVER</b>	<b>Base Spec: shall be manufacturer standard with adjustable positiona and three point lab/shoulder seat belt.</b>	
<b>SEAT, DRIVER; SEAT BELT</b>	Upgrade to cloth seat <b>Seat belts for drivers with adjustable type shoulder harness are required.</b>	B4770
<b>SEAT BARRIERS</b>	<b>Shall be equipped with the appropriate seat barriers to comply with the National Standards and FMVSS 222.</b>	
<b>SEATS, PASSENGER. NOTE: The school bus will be equipped with seats. The following are options.</b>	<b>Seats shall be supported with two-legged seat rail mounted inside the body. Padding for seats shall be as specified in National Standards Seats must meet National Standards. Minimum knee room spacing between the seats shall be 24". Fire block 42 oz. upholstery. DOT 45" high back seat.</b>	
<b>SEATS, FIRE BLOCK</b>	<b>Required</b> Upgrade to Kevlar fire block	B5070
<b>SEATS, PASSENGER: COLOR</b>	<b>Shall comply with National Standards.</b> Color other than manufacturer standard. Please notify and verify availability of color of choice.	B5090
<b>SEATS, DEDUCT FOR SEATS REMOVED</b>	<b>None</b> Deduct for base bid bench seats. Check with dealer for exact quantity.	B5100
<b>SEATS 30 INCH BENCH SEAT; FLOOR MOUNT</b>	30 inch floor mounted seat (state quantity)	B5110
<b>SEATS 30 INCH BENCH SEAT; TRACK MOUNT</b>	30 inch track mounted seat (state quantity)	B5120
<b>SEATS 36 INCH BENCH SEAT; FLOOR MOUNT</b>	36 inch floor mounted seat (state quantity)	B5130
<b>SEATS 36 INCH BENCH SEAT; TRACK MOUNT</b>	36 inch track mounted seat (state quantity)	B5140

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>SEATS 39 INCH BENCH SEAT; FLOOR MOUNT</b>		
	39 inch floor mounted seat (state quantity)	B5150
<b>SEATS 39 INCH BENCH SEAT; TRACK MOUNT</b>		
	39 inch track mounted seat (state quantity)	B5160
<b>SEAT BELT - Lap belts shall not be installed on passenger seats in large school buses (over 10,000 pounds GVWR) except in conjunction with child safety restraint systems that comply with the requirements of FMVSS No. 213, Child Restraint Systems.</b>	<b>None</b>	
<b>SEATS 30" BENCH; FL MOUNT; INTERCHANGABLE BACK</b>		
	30" floor mounted seat w/interchangable back (state quantity)	B5180
<b>SEATS 36" BENCH; FL MOUNT; INTERCHANGABLE BACK</b>		
	36" floor mounted seat w/interchangable back (state quantity)	B5200
<b>SEATS 39" BENCH; FL MOUNT; INTERCHANGABLE BACK</b>		
	39" floor mounted seat w/interchangable back (state quantity)	B5220
<b>SEATS, CHILD INT. 30 " FLOOR MOUNT - comes with 2 integrated child seats.</b>		
	30 inch seat (state quantity)	B5240
<b>SEATS, CHILD INT. 39 " FLOOR MOUNT - comes with 2 integrated child seats.</b>		
	39 inch seat (state quantity)	B5250
<b>SEATS, CHILD INT. 30" TRACK MOUNT - comes with 2 integrated child seats.</b>		
	30 inch seat (state quantity)	B5270
<b>SEATS, CHILD INT. 39" TRACK MOUNT - comes with 2 integrated child seats.</b>		
	39 inch seat (state quantity)	B5290
<b>SEATS, 3 POINT, 30" FLOOR MOUNT - includes 2 point lap/shoulder belt</b>		
	30 inch seat (state quantity)	B5430
<b>SEATS, 3 POINT, 36" FLOOR MOUNT - includes 2 point lap/shoulder belt</b>		
	36 inch seat (state quantity)	B5440
<b>SEATS, 3 POINT, 39" FLOOR MOUNT - includes 3 point lap/shoulder belt.</b>		
	39 inch seat (state quantity)	B5450
<b>SEATS, 3 POINT, 30" TRACK MOUNT - includes 2 point lap/shoulder belt.</b>		
	30 inch seat (state quantity)	B5460
<b>SEATS, 3 POINT, 36" TRACK MOUNT - includes 2 point lap/shoulder belt X</b>		
	36 inch seat (state quantity)	B5470
<b>SEATS, 3 POINT, 39" TRACK MOUNT - includes 3 point lap/shoulder belt</b>		
	39 inch seat (state quantity)	B5480
<b>SEATS, CHILD INT. 3 POINT, 30" FLOOR MOUNT</b>		
	30 inch seat (state quantity)	B5610
<b>SEATS, CHILD INT. 3 POINT, 30" TRACK MOUNT</b>		
	30 inch seat (state quantity)	B5620
<b>SEATS, CHILD INT. 3 POINT, 36" FLOOR MOUNT</b>		
	36 inch seat (state quantity)	B5630
<b>SEATS, CHILD INT. 3 POINT, 36" TRACK MOUNT</b>		
	36 inch seat (state quantity)	B5640

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>SEATS, CHILD INT. 3 POINT, 39" FLOOR MOUNT</b>		
	39 inch seat (state quantity)	B5650
<b>SEATS, CHILD INT. 3 POINT, 39" TRACK MOUNT</b>		
	39 inch seat (state quantity)	B5660
<b>STORAGE POUCH KICK PANEL BARRIER</b>	<b>None (located behind driver on barrier)</b>	
	Single pouch barrier	B5750
<b>KICK PANEL</b>	<b>One on right side</b>	
	Add additional left side front	B5780
<b>STEP; DRIVER</b>	<b>None</b>	
	Add Running board type step full width	B5790
<b>STEPWELL</b>	<b>Stepwell shall be of non - corrosive steel, all screws and bolts shall be non corrosive steel, and shall meet National Standards. It shall contain at least one light. Step shall be covered with rubberized flooring step tread.</b>	
<b>STOP ARM SIGNAL</b>	<b>Single electric incandescent arm shall be considered standard equipment. Stop arm shall be constructed of metal ribbed or reinforced panel; such stop arm shall include wind guard and be equipped with two alternating red flashing lights. Stop arm shall meet National Standards and FMVSS #131.</b>	
	Electric LED cluster	B5910
	Electric LED strobing	B5920
	Electric LED on STOP	B5930
<b>STORAGE COMPARTMENT DRIVER CONSOLE</b>	<b>None</b>	
<b>STORAGE COMPARTMENT DRIVER ABOVE DRIVER</b>	<b>None</b>	
	Add storage compartment above driver window	B6030
<b>STUDENT REMINDER SYSTEM</b>	<b>Included. Manufacturer Standard to be triggered by warning lights</b>	
	Delete Student Reminder System	B6080
<b>STUDENT REMINDER ACTIVATION</b>		
	To be armed by ignition.	B6110
	To be armed by other methods	B6120
<b>SUNSHADE/SUNSHIELD</b>	<b>Shall comply with National Standards.</b>	
<b>VENTILATION</b>	<b>Shall comply with National Standards</b>	
<b>WHEEL HOUSING</b>	<b>Shall be constructed of 18 gauge or heavier steel and be rigidly reinforced and be attached to the floor and side panels in such a manner as to prevent water or dust from entering the bus interior and shall be designed for easy removal of tires</b>	
<b>WINDOW, STORM SASH, DRIVER SIDE</b>	<b>None (not tinted)</b>	
	Add window, left side, storm sash (state quantity)	B6220
<b>WINDOW, STORM SASH, ENTRANCE DOOR</b>	<b>None</b>	
	Storm sash, upper only	B6230
	Storm sash whole door	B6240
<b>WINDOW, STORM SASH, PASSENGER</b>	<b>None (not tinted)</b>	
	Add passenger side windows, storm sash. (state quantity)	B6250
<b>WINDOW, REAR</b>	<b>Manufacturer Standard</b>	
	Tempered, Clear	B6260
	Laminated, tinted	B6270

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>WINDOWS</b>	<b>Windows shall be single pane split type construction safety glass to set in aluminum or steel frame. Emergency windows shall meet state specifications and National Rule 217. Windshield, service and emerg doors, side and rear windows may be equipped with max integral tinting allowed by fed, state, or ANSI standards for respective locations, except that windows rear of drivers compartment, if tinted, shall have approx 28% light transmission. Inside windows shall have marks indicating the half way point.</b>	
	Remove tint	B6310
	Laminated, tinted	B6320
	Laminated, clear	B6330
<b>WINDOW LINES</b>		
	Remove window lines	B6340
<b>WINDOW, SIDE SASHES</b>	<b>Shall comply with National Standards.</b>	
	Painted window side sashes black	B6380
<b>WINDOW; PILASTERS</b>		
	Paint pilasters black	B6390
<b>WINDSHIELD</b>	<b>Windshield to be OEM standard.</b>	
<b>WINDSHIELD WASHER</b>	<b>Windshield washer fluid container is to be OEM Standard and must meet State and National Standards. Reservoir shall be full upon delivery to owner and protected to 20°F below zero</b>	
<b>WIPER BLADES</b>	<b>Wipers are to be electrical, intermittent, wet arm and 2-speed. Wipers shall comply with FMVSS #104</b>	
<b>WHEELCHAIR ENTRY</b>	<b>None; If selected option the lift shall be a Braun and include a lift door, lift required lights and brake/lift interlocks to meet National Standards. Includes the deduct for the 2 seats in the lift area.</b>	
	Rear lift door w/Braun. If selected option shall include a lift door, lift required lights and brake/lift interlocks to meet National Standards. Should also include the deduct for the 2 seats in the lift area.	B6590
<b>WHEELCHAIR ENTRY ALT. BRANDS</b>	<b>None; If selected option the lift shall include a lift door, lift required lights and brake/lift interlocks to meet National Standards. Includes the deduct for the 2 seats in the lift area.</b>	
	Change to Ricon brand lift	B6640
<b>LIFT DOOR</b>	<b>Shall comply with National Standards.</b>	
	Lock on lift door	B6650
<b>EXTERIOR LIFT LIGHTS</b>	<b>Shall comply with National Standards</b>	
	Additional Exterior lift lights	B6660
<b>INTERIOR LIFT LIGHTS</b>	<b>Shall comply with National Standards</b>	
	Additional interior lift lights	B6670
<b>FLAT FLOOR PACKAGE (NO SECUREMENTS)</b>	<b>None; If selected to include all body and chassis equipment needed for flat floor. Contact Dealer before selecting this option.</b>	

<b>Product Category</b>	<b>Bus: A and AII</b>	
	Add flat floor package. If selected to include all body and chassis equipment needed for flat floor.	B6690
<b>FLOOR TRACKING SYSTEM (NO SECUREMENTS)</b>	<b>None</b>	
	4 floor rows/1 row over window/L-track. Includes 4 floor rows, 1 row over windows, L-track. State quantity of wheelchair placements. SecUREMENTS or seats not included. When choosing floor tracking systems, you will need to deduct seats. Deduct approximately 2 seats per wheelchair station. Check with dealer for exact number.	B6710
	Single row track floor only both sides	B6720
	Single row track floor right side only	B6730
	Single row track floor left side only	B6740
<b>WHEELCHAIR SECUREMENTS (L-TRACK)</b>	<b>None</b>	
	Sure-Lok 700 Series Kit (Includes 4 Retractors and Occupant Restraint System). State quantity of wheel chair stations For use w/L-Track. This option requires an in-floor track system. See option B6710	B6800
	Sure-Lok 800 Series Kit (Includes 4 Retractors and Occupant Restraint System) for use with WC 19 wheel chairs. State quantity of wheel chair stations. For use w/L-Track. This option requires an in-floor track system. See option B6710	B6810
	Q-Straint QRT Deluxe Kit (Includes 4 Retractors and Occupant Restraint System). State quantity of wheel chair stations. For use w/L-Track. See option B6710	B6840
	Q-Straint QRT 360 Kit (Includes 4 Retractors and Occupant Restraint System) for use with WC 19 wheel chairs. State quantity of wheel chair stations For use w/L-Track. This option requires an in-floor track system. See option B6710	B6850
<b>WHEELCHAIR LOCATION</b>	<b>None</b>	
	Dedicated wheel chair locations (qty). No seats, seat tracks or secUREMENTS included.	B6860
<b>WHEELCHAIR SEC. STORAGE POUCH</b>	<b>A mounted storage device for the Wheelchair Tie Down &amp; Occupant Restraint System (WTORS) SHALL BE PROVIDED for each wheel chair position. Storage device shall comply with National Standards.</b>	
<b>EVAC-AID</b>	<b>None</b>	
	Add evac-aid fire blankets (quantity)	B6950
<b>FIRE BLANKET</b>	<b>None</b>	
	Add fire blankets (state quantity)	B6960
<b>PREWIRE FOR SECURITY &amp; GPS SYSTEMS</b>	<b>None</b>	
<b>RADIO 2-WAY</b>	<b>None. Contact dealer for options</b>	
<b>PREWIRE FOR 2-WAY RADIO</b>	<b>None</b>	
	Prewire for 2-way radio. Wiring to include for battery power, ground & ignition connections	B7030

<b>Product Category</b>	<b>Bus: A and AII</b>	
<b>SURVEILLANCE CAMERA SYSTEM</b>	<b>None included but optional systems must include event marker. Contact Dealer for hardware availability and pricing if Camera System is desired. Pricing for labor and pre-wire is listed below.</b>	
	Labor to install single camera system	B7710
	Labor to install dual camera system	B7720
	Labor to install three-camera system	B7730
	Labor to install four-camera system	B7740
<b>MULTIFUNCTION BUS OPTION</b>	<b>None</b>	
	Change bus to Activity Bus. To include all changes needed to convert bus into a white colored multi-function activity school bus, removes 8-way lamps, stop arm and yellow reflective is replaced with white reflective.	B8000
<b>ACTIVITY BUS COLOR OPTION</b>	<b>White</b>	
	Custom Color Solid	B8050
<b>ACTIVITY; TRIM COLOR BUMPERS</b>	<b>Black front and rear</b>	
	Custom color on bumpers	B8070
<b>ACTIVITY BUS GRILLE COLOR</b>	<b>Oem Standard</b>	
<b>ACTIVITY BUS RUB RAIL COLOR</b>	<b>White-only if custom bus color selected</b>	
	Contrasting Color (quantity of rails). Select number of rails to have painted contrasting color	B8100
<b>GRAPHIC PACKAGE</b>	<b>None. Contact dealer for options</b>	
<b>WHITE LETTERING &amp; TRIM</b>	<b>None</b>	
	Upgrade white reflective package to sides & rear of unit for activity buses only.	B8190
<b>SEATING; ACTIVITY PASSENGER</b>	<b>None</b>	
	Activity seats (state quantity). Manufacturer standard vinyl fireblock high back split seat. Must not recline.	B8200
	Freedman seating (state quantity). Activity high back vinyl fireblock seats. Must not recline.	B8205
	3-point activity seats. (state quantity)x	B8210
<b>SEATING; ACTIVITY PASSENGER UPHOLSTERY</b>	<b>Vinyl fireblock</b>	
<b>SEATING PASSENGER ARMREST</b>	<b>None</b>	
	Add armrest (qty)	B8250
<b>STORAGE; REAR EQUIPMENT</b>	<b>None</b>	
	Add maximum rear equipment storage.	B8300
	Add small rear equipment storage	B8310
<b>STORAGE, OVERHEAD (INTERIOR LUGGAGE RACK)</b>	<b>None included. If selected, must be enclosed to meet national standards.</b>	
	Add overhead parcel racks for activity bus	B8350